

Technical Data Sheet

KSW-AQ55

Polyethylene Wax Emulsion



Kustom Wax Additives

Product Description

KSW-AQ55 is a high density poly wax emulsion developed for use in water based coatings. **KSW-AQ55** will improve slip, rub resistance, hardness and block resistance. It can be used as an additive to paper coatings, wood coatings, metal coatings, overprint varnishes, floor polish and other water based coatings where slip and hardness are required, without significant degradation of gloss.

Performance Characteristics

- Lubricity and slip
- Rub Resistance
- Film Hardness
- Block Resistance

Physical Properties

Appearance:	Light amber liquid
Wax Solids:	High Density Polyethylene
Emulsifier Charge:	Nonionic
Non-Volatile (%):	34.5 - 35.5
pH:	9.0 - 10.5
Recommended pH of your system:	> 7.0

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 03/08/2017