

Technical Data Sheet

KB-1083

Prop 65/BPA Free, Mineral Oil
Free S.F. Low Tack Extender



**KUSTOM
GREENMASTER**

Product Description

KB-1083 is intentionally formulated without ink oil/mineral oil or hydrocarbon resin of any type. This is related to food packaging in an indirect contact application. **KB-1083** is 100% solids but maintains very fast set speed in an ink. **KB-1083** is formulated with high end resins to exhibit excellent litho properties.

Performance Characteristics

- Contains no ink oil/mineral oil or Hydrocarbon Resin.
- Formulated with Prop 65 Free raw materials
- Considered low odor and low migration for food packaging applications
- Formulated with materials from the Nestle positive list
- Fully composed of substances set out in Annex 1 & in Annex 10 of the ordinance FDHA of materials & articles (817.023.21)
- Can conform to US FDA CFR 175.300 & 175.320 if certain specifications and limitations are met.
- Excellent litho and set speed properties.
- High Solids

Physical Properties

Tack @ 1200 RPMs @ 1':	14.0 - 16.0
Viscosity in Poises:	175- 250
Yield Value in Dynes/cm2:	2000 - 3000
% Solids:	98 - 100%

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 09/10/2018