

# Technical Data Sheet

## KBW-PY500

## POLYTECH 500

100% Solids, High Performance

PTFE/Polyethylene Wax Compound

---



*Kustom Wax Additives*

### Product Description

---

**KBW-PY500** contains the perfect ratio of low coefficient of friction (COF) high performance polyethylene/PTFE in compound form. This proprietary mixture will provide a smooth, scuff resistant finish to the printed film. Recommended for sheetfed applications.

### Performance Characteristics

---

- Outstanding rub resistance
- Good gloss retention
- Effective on non-porous substrates and in low VOC formulations
- Excellent set speed

### Usage Recommendation

---

3 - 5%

### Physical Properties

---

|                 |                   |
|-----------------|-------------------|
| % Non-Volatile: | 96 - 100%         |
| Polymer Type:   | PTFE/Polyethylene |

---

#### **FOR YOUR PROTECTION:**

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own application. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the SDS for additional information. DATE REVISED: 01/18/2019