

Technical Data Sheet



KB-1074

Prop 65 Free High Solids SF Gel Vehicle

Product Description

KB-1074 is formulated to exhibit high viscosity and excellent heat and shear stability, with an all BPA free phenolic-based resin system. This vehicle creates an ink that will not break down on high speed presses and will maintain dot sharpness. Ink made with **KB-1074** is suitable for many high solids sheetfed applications including carton inks.

Performance Characteristics

- High solids
- High viscosity
- Excellent litho properties
- BPA free, Naphthalene free, Formaldehyde free

Physical Properties

Tack @ 400 RPMs/1':	18 - 22
Viscosity in Poises:	1500 - 2000
Yield Value in Dynes/cm2:	20,000 - 30,000
% Solids:	98 - 100

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 01/25/2019