

Technical Data Sheet

KB-1921

High Speed Sheetfed Vehicle



Product Description

KB-1921 is a product designed to meet the latest demands placed on ink makers. As press speeds increase and printers demand flexibility in the sheetfed ink, vehicles will need to offer increased levels of viscosity relative to tack and also remain stable over a wide range of temperatures.

This concept should provide the ink maker with a system that lends itself to both waterless and lithographic technologies.

Performance Characteristics

- Temperature stability
- Waterless printing stability
- Good viscosity-to-tack ratio
- Medium gel body

Physical Properties

Tack @ 400 rpm/1 minute:	10-12
Viscosity (Poise):	1000-1300
Yield (dynes/cm²):	20000-30000
Solids:	71-73%

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC. , and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 02/21/2019