

# Technical Data Sheet



## KB-280

100% NVM Low Dot Gain  
Soya Gel Vehicle

---

### Product Description

**KB-280** is formulated to exhibit high viscosity and excellent heat and shear stability. This vehicle creates an ink that will not break down on high speed presses and will maintain dot sharpness. Ink made with **KB-280** is suitable for many high solids sheetfed applications including carton inks.

### Performance Characteristics

- 50% Soya Oil Content to Satisfy Any Labeling Requirements.
- High Solids
- Excellent Litho Properties
- Fast Set Speed

### Physical Properties

<b>Tack @ 400 RPMs/1':</b>	12.5 -13.5
<b>Viscosity in Poises:</b>	400 - 650
<b>Yield Value in Dynes/cm2:</b>	15,000-20,000
<b>% Solids:</b>	98 - 100

#### FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 04/01/2019