

Technical Data Sheet

KBW-PT400

PTFE Compound



KBW-PT400 is our highest PTFE containing compound. **KBW-PT400** imparts excellent rub performance and increases slip. **KBW-PT400** provides a laser resistant film and maintains excellent gloss. **KBW-PT400** is recommended for use in sheetfed and heatset inks.

Performance Characteristics

- ~60% PTFE loading
- Lowers surface tension and improves slip
- Excellent rub resistance
- Good gloss retention
- Laser safe, heat stable

Usage Recommendation

1 – 4%

Physical Properties

% Non-Volatile:	96 - 100%
Polymer Type:	PTFE
Appearance:	Off-White Paste

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their application. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for any specific application, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the SDS for additional information. DATE REVISED: 04/10/2019