

# Technical Data Sheet

## KSW-AQ60

Paraffin/Polyethylene Wax Emulsion



*Kustom Wax Additives*

### Product Description

---

**KSW-AQ60** is a nonionic paraffin/polyethylene wax emulsion developed for use in water based coatings. **KSW-AQ60** improves water resistance, mar resistance and anti-block properties in coatings. It can be used as an additive in paint and coatings, inks and OPV's, and other water based products.

### Performance Characteristics

---

- Block Resistance
- Water Resistance
- Mar Resistance
- Heat Resistance

### Physical Properties

---

Appearance:	White, opaque liquid
Wax Solids:	Paraffin/ Polyethylene wax blend
Emulsifier Charge:	Nonionic
Non-Volatile (%):	29.0 – 31.0
pH:	8.5 - 9.5
Recommended pH of your system:	> 7.0

#### **FOR YOUR PROTECTION:**

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own specific use. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for any specific application, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 07/29/2019