

KB-633 Technical Data Sheet

KB-633

Fast Setting, Laser Resistant Heatset F.F. Vehicle



Product Description

KB-633 is formulated to be extremely fast setting and allow for high-speed heatset printing even with short ovens. The fast setting and hard drying nature of **KB-633** will eliminate many problems with marking through the delivery, chill rolls, and bindery process. Use as a companion free flow vehicle for **KB-673LT** fast setting gel vehicle.

Performance Characteristics

- Ultra fast set speed
- Excellent gloss
- Superb litho properties

Physical Properties

Tack @ 400 rpm/1 min:	20.0 – 22.5
Viscosity in Poise:	1000 – 1200
Yield Value in Dynes/cm²:	3,500 – 5,500
% Solids:	45-50
Specific Gravity:	0.84

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 10/22/2018