# Technical Data Sheet KB-750 Kentucky Lube Anti-Picking Additive



#### **Product Description**

**KB-750** is an additive for any litho ink system that will provide lubrication of the ink on the plate and blanket cylinders. When used at a 2-5% level **Kentucky Lube** is useful in preventing piling and picking problems on press. This is especially important when printing on lighter weight papers and recycled stocks that often cause piling, linting, and hickey problems on press. Inks can be made at the desirable higher tacks with **KB-750** to maintain dot sharpness and still will NOT pick. **Kentucky Lube** will NOT adversely affect other ink properties on press or the printed sheet.

### **Performance Characteristics**

- Very Effective in Preventing Piling
- Reduces Misting by Allowing You to Increase Tack Without Picking
- Improves Transfer

## **Physical Properties**

Viscosity Solids 150-250 Poise 89 – 91%

#### FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC. and users should made their own tests to determine the suitability of this product for their own application. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for any specific application other than that the material conforms applicable to current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 08/12/2019