

Technical Data Sheet

KB-406

100% NVM Fast Setting SF
Flushing Vehicle



Product Description

KB-406 is a high solids hard drying flushing vehicle. It is an excellent choice for all nonporous substrates to promote positive dry and adhesion. **KB-406** promotes high holdout, with excellent gloss and transfer properties.

Performance Characteristics

- Excellent pigment wetting
- High oxidative potential
- Excellent water balance and litho performance.
- Excellent gloss

Physical Properties

Tack @ 400 RPMs @ 1':	16.5 – 19.0
Viscosity in Poise:	350 – 450
Yield Value in Dynes/cm²:	N/A
% Solids	98 – 100%

FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC. , and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 01/18/2018