

# Technical Data Sheet



## KB-215

### Lithomaster S.F. Vehicle



## Product Description

**KB-215** is a unique development in sheetfed vehicle technology and is specially formulated to allow your inks to exhibit unique body and flow properties. This will result in vastly improved transfer and litho performance on today's high-speed presses. To further enhance the performance of this system, we have developed several companion vehicles, including dispersion and flushing vehicles. Bases prepared from these vehicles will also aid in improving the performance of your inks. This is a different approach in vehicle chemistry that deserves an in depth evaluation by quality-minded ink makers.

## Performance Characteristics

- Very low dot gain.
- Better transfer and color stability during long press runs.
- Excellent water balance and litho performance.
- Good work and turn characteristics with high gloss.

## Physical Properties

<b>Tack @ 400 RPMs @ 1':</b>	16.5 -19.0
<b>Viscosity in Poises:</b>	900-1,100
<b>Yield Value in Dynes/cm2:</b>	5,000-8,000
<b>% Solids:</b>	85 - 87
<b>NAPIM Bio Renewable Content (BRC)</b>	65 - 75%

### FOR YOUR PROTECTION:

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of KUSTOM GROUP, INC., and users should make their own tests to determine the suitability of this product for their own particular purposes. However, because of numerous factors affecting results, KUSTOM GROUP, INC. makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for particular purpose, other than that the material conforms to its applicable current Standard Specifications. Standard Specifications, although current at the time of publication, are subject to change without notice. Please refer to the MSDS for additional information. DATE REVISED: 12/09/2019