

# KB-1098 EU

## Gloss Varnish

### Description

KB-1098 EU is a sheetfed gloss varnish designed for use in the highest quality offset ink systems and 3 piece metal deco inks. The KB-1098 EU gloss varnish is based on phenolic modified rosin resins and vegetable oils. The set speed of this product is exceptional for vehicles of this type, and drying can be controlled by varying the amounts and types of ink driers. KB-1098 EU is compatible with a wide variety of commonly used vehicles and modifiers, including soya systems. KB-1098 EU improves transfer due to higher tack and has a high water repellency in 3 piece metal deco inks.

### Performance Characteristics

- Mineral Oil Free and Swiss Ordinance compliant
- Excellent Film and Resistance Properties
- Excellent Water Fighting with High Viscosity
- Improves transfer due to high tack
- High Gloss

### Safety Datasheet

Available on request

Specifications		Values	Method of analysis
Tack		400-500	30°C - 100 m/min
Viscosity	dPa.s	3000 – 5000	23°C – C&P (Eurocommit)
Non-Volatile	%	98-100	
Tan Delta		3,0-5,0	25°C

#### Notice:

The presented information is accurate to be the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.



[www.csm.umicore.com](http://www.csm.umicore.com)

**Umicore Specialty Materials Brugge NV**

Kleine Pathoekeweg 82  
8000 Brugge, Belgium

Tel.: +32 50 320 720  
[Info.USMB@eu.umicore.com](mailto:Info.USMB@eu.umicore.com)  
[www.csm.umicore.com](http://www.csm.umicore.com)