

KB-480 EU

General Purpose Sheetfed Pigment Dispersion Vehicle

Description

KB-480 EU is a general purpose sheetfed dispersion vehicle with good wetting and litho performance. It's formulated to be higher solids and its resin system allows for good dispersion properties. KB-480 EU when used in conjunction with KB-1104 EU, general purpose let back vehicle, promotes high performance on press, while maintaining a cost-efficient ink system for paper and paperboard.

Performance Characteristics

- Excellent pigment wetting properties
- Good oxidative potential
- Excellent water balance and litho performance
- Excellent gloss
- Economical Vehicle

Safety Datasheet

Available on request

Specifications		Values	Method of analysis
Tack		150 – 250	30°C - 100 m/min
Viscosity	dPa.s	300 – 500	25°C – C&P 10s-1
Non-Volatile	%	84 – 86	

Notice:

The presented information is accurate to be the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.



www.csm.umicore.com

Umicore Specialty Materials Brugge NV

Kleine Pathoekeweg 82
8000 Brugge, Belgium

Tel.: +32 50 320 720
Info.USMB@eu.umicore.com
www.csm.umicore.com